

MANUFACTURER	John Deere
MODEL	667A Model Year 2008
Engine	
Manufacturer	Kawasaki
Model No.	FH680V
Horsepower (gross)	23 hp (17 kW)
Displacement	41.2 cu. in. (675 cc)
Cylinders	Two
Crankcase Capacity	2 U.S. qt. w/filter
Oil Filter	Full flow, replaceable
Lubrication	Full pressure
Cooling	Air
Air Cleaner	Heavy duty canister type
Pre-Cleaner	Foam
Fuel System	
Fuel Type	Regular unleaded gasoline
Fuel Tank Capacity	6 U.S. gallons (22.7 L)
Fuel Tank Switch/Shut Off Valve	Yes
Fuel Consumption	---
Electrical System	
Charge System	13 amp
Battery Voltage	12 volt
Cold Cranking Amp	340
Hour Meter	Yes
Operator Presence Starting System	Yes
Drive Train	
Hydraulic Pumps	Kanzaki DUP 10A
Wheel Motors	Parker Ross, 195 cc/rev
Travel Speed	8 mph
Forward	0-8 mph (0-12.9 km/h)
Reverse	0-4 mph (0-6.43 km/h)
Speed and Direction Control	Twin hand-control
Hydraulic Capacity	Hydraulic System Cap. 2.5 U.S. gal.
Hydraulic Oil Cooler	---
Filter	Spin-on type
Tires	
Drive Tires	20x10-10 turf
Rear Tires	---
Load Rating	4 PR
Brakes	
Dynamic Braking	Dual hand-control
Park Brake	Tire stop
Park Brake Actuation	Hand lever
PTO	
Type	Warner Magstop
Drive	V-belt
Mower Decks	
Available Widths	60 in.
Deck construction	7-Iron: One piece stamped steel
Deck thickness	7 gauge (.177 in.) stamped
Discharge	Side, 18-in.
Height-of-Cut Range	1.5 - 5.0 in.
Increments	0.25 in.
Cutting Width	60 in.
Blades	
Length	21 in. (60 in. deck)
Thickness	0.25 in.
Tip Speed	18,000 fpm
Number	Three, 1.5 in. overlap

Wheels

Caster Wheel Type	Rubber, pneumatic
Caster Wheel Size	13x5-6
Front Anti-Scalp Rollers	RH, center, LH
Rear Anti-Scalp Rollers	LH

Dimensions

Length	69.5 in.
Width	74 in.
Height	48 in.
Weight	1067 lb.

Specifications are based on published information at the time of publication. Specifications are subject to change without notice. Contact [your local John Deere dealer](#) for more information.