

# 65E / Motor Grader TURBO



110 HP  
16,800 LBS  
10' or 12' BLADE

Pictured with optional equipment

## Compact Grader With Big Grader Features

53" Circle With "A" Frame Drawbar

Full Power Shift Transmission With Torque Converter

Torque Proportioning Rear Differential

*Built From A Lineage Of Market Leaders For Over 50 Years*



# 65E / Motor Grader TURBO



## BIG GRADER FEATURES IN A SMALL PACKAGE

### Operating Weight

- Front 4,700 lb
- Rear 12,100 lb
- Total 16,800 lb

### Engine

- Make/Model Cummins QSB4.5
- Type 4 Cycle, turbo diesel
- No. of cylinders 4
- Displacement 275 cu. in.
- Horsepower 110
- Rated speed 2,200 rpm

### Brakes

- Service – 4 wheel, wet disc & self adjusting
- Independent tandem by tandem system
- Mechanical parking brake

### Axles

- Front axle clearance – 20.3"
- Rear axle – torque proportioning differential

### Transmission

- Full power shift with torque converter
- 6 speeds forward – top speed 24 mph
- Electronic shift control
- LCD message center
- Shift inhibit system

### Circle

- 53" diameter gear driven circle
- Supported on 4 guides with wear plates
- Shim adjustable
- 360° rotation
- Hydraulic circle side shift

### Moldboard/Blade

- "Rollaway" blade with end bits
- Replaceable cutting edges
- Size – 10' x 16.63" x 0.63"
- Lift above ground – 15.4"
- Maximum penetration – 20"



Full power shift transmission with torque converter



53" gear driven circle with "A" frame allows 360° blade rotation




Illustration includes optional equipment

## STANDARD EQUIPMENT

- Accelerator/decelerator and hand throttle
- Alternator – 100 Amp.
- Articulated frame
- Back-up alarm
- Batteries (2) – 12 volt
- Controls, hydraulic
  - Articulation
  - Circle side shift
  - Circle turn
  - Moldboard lift/lower
  - Moldboard side shift
  - Wheel lean
- Control console, adjustable
- Drawbar
- Engine side panels
- Gauges
  - Air cleaner service indicator
  - Engine coolant temperature
  - Engine oil pressure
  - Fuel level
  - Hourmeter
  - Transmission LCD message center
  - Transmission oil temperature
  - Voltmeter
- Horn, electric
- Implement control lever lock
- Light package
  - Front headlights (2) – hi/lo beam
  - Front worklights (2)
  - Turn signals, stop and tail lights
- Master electrical switch
- Mechanical parking brake
- Muffler, horizontal under hood
- Moldboard – 10' wide
- Moldboard pitch, manual
- ROPS Canopy with
  - Dome light
  - Floor mat
  - Glove box
  - Grab handles
  - Headliner
  - Inside mirror
  - Seat belt
- Seat, vinyl – deluxe air suspension
- Steps, right and left
- Tires – 15.00 x 19.5 (8PR) G2 tubeless
- Valve eight station
- Vandalism protection

## OPTIONAL EQUIPMENT

- Cab, includes
  - Cloth seat – air suspension
  - Defroster fans (2)
  - F & R wipers/washers
  - Heater, 40,000 BTU
  - Inside mirror
  - Sliding rear window
  - Sound suppression
  - Tinted glass
- Cold weather starting aid (ether)
- Dozer – 8' x 2', with skid plates
- Factory air conditioner
- Float control valves, (3)
- Floodlights, (2) F & (2) R
- Mirrors, rearview – external, (2)
- Moldboard – 12' wide
- Moldboard extensions
- Moldboard pitch, hydraulic
- Rear ripper – 75" wide, 3 shanks
- Scarifier – 41" wide, 9 teeth
- Strobe light
- 90° bank slope saddle



Deluxe cab



Scarifier



Dozer blade



90° Bank slope saddle



NorAm Construction Equipment  
1250 W. Northwest Hwy., # 504  
Palatine, IL 60067  
847-934-6565

The information contained in this brochure is intended to be of general nature only. The manufacturer may at any time and from time to time, for technical or other necessary reasons, modify any of the details or specifications of the product described in this brochure. Illustrations do not necessarily show products in standard condition. The dimensions, weights and capacities shown herein, as well as any conversion data used, are approximate only and are subject to variations within normal manufacturing techniques. To be sure of getting accurate, detailed and up-to-date information, any intending buyer should contact NorAm.