

ZTrak™ Mowers

Z700 Series



JOHN DEERE



Go into business with a solid performer.

If you are a part-time commercial mower, take a look at the zero-turn mowers that can accommodate both your ambitions and your budget: the new ZTrak™ Z700 Series Mowers from John Deere.

With several heavy-duty, commercial-grade features, the Z700 will give you the ability to tackle any kind of mowing job you may encounter.

Z700 SERIES MODELS

Z710A 23-hp/48-in. 7-Iron™ II mower deck

Z710A 23-hp/54-in. 7-Iron™ II mower deck

Z720A 25-hp/60-in. 7-Iron™ II mower deck



Z720A



Z700 Series Features

If you're looking to invest in a commercial-grade mower, the best place for you to start is with a ZTrak Z700 model. From performance to convenience, you'll find a mower you can do business with.



Height-of-cut adjustment dial

Set your cut height right from your seat. This simple mechanical design ensures great performance and long life. A transport lock keeps your deck in place when loading and unloading.



BRAKE & GO™ System

To start a Z700, all you have to do is set the parking brake with your foot and turn the key. That's it. You don't have to worry about what position the control levers are in. Just brake.....and go.



Reinforced Deck Spindle

The one-inch cold-forged spindles are heat-treated for strength and are supported by ball bearings. The spindle housings are made of ribbed cast aluminum for both strength and heat dissipation.



Powerful Engine

Both the Z710A and Z720A are powered by the air-cooled Kohler Command PRO® commercial engine. It features an overhead valve design for more torque and a true dual-stage air filtration system.



Large 7-Gallon Fuel tank

This large capacity tank is equipped with a large filler neck for easy refueling. The easy-access fuel gauge lets you know how much fuel is left. And the top draw gives an added measure of safety.



Gear reduction drive

Made to perform. A gear reduction drive in the wheel motor adds mechanical muscle, increasing the torque available over a purely hydraulic system. Contains a 10cc piston style pump with matching wheel motor.



7-Iron II™ Commercial Mower Deck

Every 7-Iron II deck is stamped from thick 7-gauge steel, using four million pounds of pressure. The result is a deep-deck design that delivers excellent airflow and fewer sharp corners for reduced material buildup. The 7-Iron II deck also features 1-in. cold-forged spindles and an impressive 18,000 f/m blade tip speed.

AVAILABLE ATTACHMENTS

Available attachments for the ZTrak 700 models include:

- 2-bag Material Collection System
- Trash kit
- Light kit
- Engine guard
- Optional rear anti-scalp wheels
- Bumper
- Mulch kit

ZTrak 700 Series



Specifications

	Z710A	Z720A
Engine		
Manufacturer	Kohler	Kohler
Horsepower (gross)*	23 hp (17.2 kw)	25 hp (18.6 kw)
Displacement	674cc	725cc
Crankshaft Orientation	Vertical	Vertical
Crankcase Capacity	2.0 U.S. quart (1.89 L)	2.0 U.S. quart (1.89 L)
Cooling	Air	Air
Air Cleaner	Heavy-duty dual stage	Heavy-duty dual stage
Fuel System		
Fuel Tank Location	Left side	Left side
Fuel Type	Gas	Gas
Fuel Tank Capacity	7 U.S. gallons (26.5 L)	7 U.S. gallons (26.5 L)
Electrical System		
Ignition	Solenoid shift	Solenoid shift
Hour Meter	Standard, digital	Standard, digital
Operator Presence Starting System	Brake & Go™ (standard)	Brake & Go™ (standard)
Drive Train		
Hydraulic Drive	Tuff-Torq® 10cc piston w/gear reduction	Tuff-Torq® 10cc piston w/gear reduction
Hydraulic Capacity	2.95 U.S. quarts per side (2.79 L)	2.95 U.S. quarts per side (2.79 L)
Filter	Internal, replaceable	Internal, replaceable
Travel Speed Forward	0-10 mph (0-16.1 km/h)	0-10 mph (0-16.1 km/h)
Travel Speed Reverse	0-4.5 mph (0-7.2 km/h)	0-4.5 mph (0-7.2 km/h)
Tires		
Drive Tires	22x9.5-12 Turf (48 in. deck) 22X11-10 (54 in. deck)	22x11-10
Front Caster Wheels	pneumatic, round shoulder 13x5-6	pneumatic, round shoulder 13x5-6
Brakes		
Park Brake	Internal wet disk	Internal wet disk
Park Brake Activation/Deactivation	Foot pedal	Foot pedal
PTO		
Type	Electro-magnetic (125 lb. ft.)	Electro-Magnetic (200 ft.-lbs.)
PTO Activation/Deactivation	Pull knob	Pull knob
Mower Decks		
Available Side Discharge Widths	48 in. & 54 in. (121.9 cm) & (137.2 cm)	60-in (152.4 cm)
Deck construction	One-piece stamped steel	One-piece stamped steel
Deck thickness	7 ga. (0.177 in.)	7 ga. (0.177 in.)
Height-of-Cut Range	1.5-5.0 in. (3.8-12.7 cm)	1.5-5.0 in. (3.8-12.7 cm)
Increments	0.25 in. (0.6 cm)	0.25 in. (0.6 cm)
Blade Tip Speed	18,000 f/m	18,000 f/m
Anti-Scalp Wheels		
Front Anti-Scalp Wheels	Double captured right, center, and left	Double captured right, center, and left
Rear Anti-Scalp Wheels	Optional	Optional
Dimensions		
Length	84 in. (213.4 cm)	84 in. (213.4 cm)
Width (deck chute down)	62 in., 68 in. (157.5, 172.7 cm)	74 in (188 cm)
Height with ROPS up	73 in. (185.4 cm)	73 in. (185.4 cm)
Height with ROPS Down	47 in (119.4 cm)	47 in (119.4 cm)
Ground Clearance	5 in. (12.7 cm)	5 in. (12.7 cm)
Weight	1092lb, 500 kg (48 in) 1107 lb, 507 kg (w/54" deck)	1132 lb (518 kg)
Warranty		
	2 year or 700 hour commercial warranty	2 year or 700 hour commercial warranty

* The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less.



This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification and design of all products described in this literature without notice.

JohnDeere.com/MowPro